

Compression latches with key-type knob

Zinc alloy

MATERIAL

Rotor, stator and knob in nickel-plated zinc alloy.

NUT

M19x1 in brass.

SPRING WASHER

Zinc-plated steel.

WASHER

PVC (only for CML. execution).

CLOSING LEVER

Zinc-plated steel, thickness 2.5 mm.

SCREW

M5x8 zinc-plated steel.

STANDARD EXECUTIONS

- **CM.**: with knob without transversal hole for the padlock.
- **CML.**: with knob provided with a transversal hole for the insertion of a padlock with hook of a diameter from 5 to 7 mm.

ROTATION





90°.

SPECIAL EXECUTIONS AND ACCESSORIES


- Closing levers in other dimensions.
- Brass threaded extension for prolonged positioning of the lever (code 421137 C.PQ M5/58).




Drilling template



CM.



CML.



CM.

Code	Description	H	D	I	l1	l2	h	ΔΔ
421211	CM.32-20	32	36	16	20	20	15	63
421213	CM.36-25	35.5	36	16	20	25	15	65

CML.

Code	Description	H	D	I	l1	l2	h	ΔΔ
421221	CML.32-25	32	36	16	25	25	23	74
421223	CML.36-30	35.5	36	16	25	30	23	76

